

ANSCHÜTZ

EINFACH **EINS** WERDEN!

1782



MANUAL

MODEL

1782

J.G. ANSCHÜTZ GmbH & Co. KG

Jagd- und Sportwaffenfabrik

Daimlerstraße 12 · 89079 Ulm / Germany

Phone +49 - (0)731- 40 12 - 0 | Fax +49 - (0)731- 40 12 - 700



www.anschuetz-sport.com



www.facebook.com/OfficialAnschuetz



www.instagram.com/AnschuetzGmbH



www.youtube.com/AnschuetzGmbH

Status as of 07 | 2024

CONTENTS

1. COMPONENTS/DEFINITIONS	4	8.8. BARREL/BARREL THREAD	22
2. INTRODUCTION	5	8.8.1. Dismounting/mounting the barrel thread	22
3. SYMBOLS USED	5	8.8.2. Dismounting/mounting the barrel	22
3.1. GENERAL NOTES	5	8.8.3. Maintenance of the barrel	23
3.2. SAFETY NOTES	5	8.8.3.1. Cleaning the barrel	23
4. GENERAL HANDLING OF GUNS	6	8.9. SIGHTS/MOUNTING	24
4.1. IMPORTANT PRINCIPLES	6	8.9.1. Adjusting the fast acquisition sight	24
4.2. SHOOTING	7	9. MAINTENANCE/CLEANING	26
4.3. MAINTENANCE	8	9.1. GENERAL	26
4.4. TRANSPORT	8	9.2. MAINTENANCE INTERVALS	27
4.5. STORAGE	8	9.2.1. Before shooting	27
4.6. EAR AND EYE PROTECTION	8	9.2.2. After shooting	27
5. LAWS	8	9.2.3. Annually	27
6. PROPER USE	8	10. TROUBLESHOOTING	28
7. LIABILITY	8	11. DISPOSAL	28
8. PRODUCT-SPECIFIC HANDLING	9	12. MISCELLANEOUS	28
8.1. BOLT	9	13. SHOOTING PERFORMANCE	28
8.1.1. Cocking the bolt	9	14. GUARANTEE CARD	29
8.1.2. Inserting the bolt	10		
8.1.3. Removing the bolt	10		
8.2. MAINTENANCE OF THE BOLT	11		
8.2.1. Components/definitions	11		
8.2.2. Disassembling the bolt	11		
8.2.3. Assembling the bolt	12		
8.3. MAINTENANCE INTERVALS FOR BOLT	12		
8.4. SETTING/RELEASING THE SAFETY	12		
8.4.1. Setting the safety	13		
8.4.2. Releasing the safety	13		
8.4.3. Bolt Handle lock	13		
8.5. LOADING/REPEATING/SHOOTING/UNLOADING	13		
8.5.1. Loading the magazine	13		
8.5.2. Repeating	15		
8.5.3. Ready to fire	16		
8.5.4. Unloading/making ready for storage	16		
8.6. TRIGGER	18		
8.6.1. Single stage trigger 5082	18		
8.6.2. Setting the trigger	18		
8.6.2.1. Adjusting the trigger blade	18		
8.6.3. Maintenance of the trigger	19		
8.6.4. Checking the trigger fastening	19		
8.7. BARRELED ACTION MOUNTING AND STOCK SETTINGS	20		
8.7.1. Components/definitions	20		
8.7.2. Mounting/dismounting the stock and barreled action	20		
8.7.3. Stock adjustments	20		
8.7.3.1. Adjustment of the cheek piece	20		
8.7.3.2. Adjustment of the stock length and the cheek piece of the GRS Bifrost stock	21		
8.7.3.3. Mounting of the sling swivel (optional)	21		
8.7.4. Maintenance/cleaning of the stock	21		

1. COMPONENTS/DEFINITIONS




Fig. 1 Overview using the example of the 1782 Classic PRO

- | | | | |
|--|------------------------------|------------------------|----------------------------|
| 1. Walnut stock, oiled,
with adjustable cheek piece | 5. Bolt catch | 10. Rubber butt plate | 15. Magazine release lever |
| 2. Bolt handle lock | 6. Bolt | 11. Sling swivel studs | 16. Magazine |
| 3. Safety | 7. Receiver | 12. Checkering | |
| 4. Bolt handle | 8. Barrel | 13. Trigger | |
| | 9. Muzzle with barrel thread | 14. Trigger guard | |

NOTE:



Your rifle may differ from the product depicted since this varies depending on model and equipment.

NOTE:



The technical data do not apply to the entire model range.
Specific model data may be found at www.anschuetz-sport.com



Fig. 2 Model variant 1782 Classic



Fig. 3 Model variant 1782 Classic PRO



Fig. 4 Model variant 1782 Black Line



Fig. 5 Model variant 1782 Gold Line



Fig. 6 Model variant 1782 German stock



Fig. 7 Model variant 1782 thumbhole stock



Fig. 8 Model variant 1782 GRS Bifrost

2. INTRODUCTION

Dear Friend of ANSCHÜTZ:

You must be able to rely on a rifle's good qualities.

For example, its exact, consistent shooting performance. The ANSCHÜTZ barrels and detailed, sophisticated bolt construction guarantee you the best gunsmith quality.

ANSCHÜTZ incorporates more than 160 years' experience into its manufacturing of precision rifles. But of course tradition isn't everything. You will always be well-equipped with absolutely reliable, easy-to-handle ANSCHÜTZ rifles.

Our hunting and target rifles are highly complex, coordinated systems. If you are not sure of how to operate and safely handle firearms, please ask us or your specialized dealer to prevent any possibly expensive repairs.

We have put various instruction manuals and possible settings for our products on our YouTube channel www.youtube.com/AnsuetzGmbH.

You can always count on the first-class quality of an ANSCHÜTZ rifle. Your ANSCHÜTZ rifle will always be a reliable companion with unmatched accuracy and function.

Your ANSCHÜTZ team

3. SYMBOLS USED

In these Manual, the following symbols are used for general and especially important details:

3.1. GENERAL NOTES

- ▶ Identifies an action instruction
- ✓ Identifies the result of an action
- Identifies a list
- ↪ Identifies a note/additional information

3.2. SAFETY NOTES

- ⚠ Identifies a safety note

OBSERVE!



Observe the instructions for use

NOTE!



Prohibition that prescribes particular behavior

NOTE!



Hearing protectors should be used for your safety!

NOTE!



Eye protection should be used for your safety!

CAUTION!



Indicates a dangerous situation that can cause bodily injuries, property damage or death.

4. GENERAL HANDLING OF GUNS

Guns can be dangerous objects, whose storage and use require particular caution. The following safety notes and warnings must absolutely be followed!

NOTE!



Before using a firearm, you must absolutely read all of the Manual.
You may only give the firearm to someone else with these Manual.

NOTE!



The firearm laws of the country in question are authoritative and must be observed.

NOTE!



In addition to reading these Manual, please have your specialized dealer explain your firearm and train you in its use.

4.1. IMPORTANT PRINCIPLES

NOTE!



It is expressly recommended that you never use firearms under the influence of drugs, alcohol or medications.
Your sight, dexterity, and judgment may be compromised. Good physical and mental health is the prerequisite for the use of a firearm. (Please also heed the currently valid legal framework.)



The use of a firearm is exclusively permitted for proper use.



Firearms owners are responsible for ensuring that their firearm is always, and especially during their absence, never within reach of and secure against access by children and other unauthorized persons.



Weapons may never be given to unauthorized persons.



Only original ANSCHÜTZ magazines may be used.



The specified capacity of the magazine may never be exceeded.



Changes to the rifle or the use of non-original ANSCHÜTZ magazines and accessories may cause malfunctions.



Severe and life-threatening injuries and damage can be caused by the use of incorrect ammunition, soiling in the barrel or incorrect cartridge components.



Firearms that exhibit safety-compromising changes may not be used. If you determine a defect or failure, the firearm must be unloaded and brought to an authorized gunsmith for repair.



In case of external effects (e.g., corrosion, dropping, etc.), the firearm must be checked by an authorized gunsmith.



A firearm must always be handled with the greatest of care and secured against falling.

4.2. SHOOTING

WARNING!



Peril to life and causing of property damage! Aiming with the muzzle at people and objects.

- ▶ When the firearm is not being used, hold the muzzle in a safe direction.
- ▶ A muzzle may never be held in a direction in which it can cause damage or endanger life.

CAUTION!



Malfunction when shooting! Shot did not release when the trigger was pulled.

- ▶ Do not look into the muzzle.
- ▶ Hold the muzzle in a safe direction.
- ▶ Unload the firearm.
- ▶ Remove residues from the barrel.

- ⚠ When ready to fire, never hold the muzzle of a firearm under water or on materials or objects in order to prevent an accident or damage to your rifle.
- ⚠ Only shoot the caliber specified on the barrel of the firearm.
- ⚠ Only clean, factory-loaded, new ammunition in the caliber approved for the rifle may be used.
- ⚠ Ammunition must comply with the specifications of the C.I.P.
- ⚠ Only load the firearm immediately before use.
- ⚠ Only original ANSCHÜTZ magazines may be used.
- ⚠ The specified capacity of the magazine may never be exceeded.
- ⚠ The use of incorrect ammunition, soiling in the barrel or incorrect cartridge components can cause life-threatening injuries and property damage.
- ⚠ Only original ANSCHÜTZ parts may be used.

- ⚠ Every firearm must be treated as if it were loaded.
- ⚠ Never pick up a firearm by the trigger.
- ⚠ Shooting ranges must be sufficiently ventilated.
- ⚠ A bullet trap in the shooting range must be completely safe and visible.
- ⚠ When shooting, no people may linger near the target.
- ⚠ In case of poor visibility conditions, a firearm should not be used.
- ⚠ Do not shoot into the air, at hard or smooth surfaces, bodies of water, or targets on the horizon.
- ⚠ Do not shoot at targets off which the bullet can ricochet or be diverted.

4.3. MAINTENANCE

- ⚠ Before and after use, or in case of maintenance and cleaning work, ensure that the firearm is not loaded.

4.4. TRANSPORT

- ⚠ Firearms may only be transported unloaded and in locked containers.
- ⚠ If you transport your firearm in a suitcase or a soft case, always make sure that the firearm and the inside of the suitcase or soft case are dry.
- ⚠ Only transport weapons in a dry and clean condition.

4.5. STORAGE

- ⚠ Firearms that are not in use must, in compliance with the currently applicable laws, be kept under lock and key.
- ⚠ Firearms must always be stored unloaded and uncocked.
- ⚠ Ammunition must be kept in a separate place under lock and key.

4.6. EAR AND EYE PROTECTION

NOTE!



When shooting, approved eye protection should be used for your safety! Shooting without safety equipment can cause vision damage.

NOTE!



When shooting, approved hearing protectors should be used for your safety! Shooting without safety equipment can cause hearing damage.

5. LAWS

NOTE!



The valid firearm laws, regulations, and provisions of the country in question as well as the safety rules of hunting and sports ordinances must be heeded.

6. PROPER USE

ANSCHÜTZ rifles are to be used exclusively for shoots and on shooting ranges (for sport and hunting disciplines) and may only be used by people with proper firearms permits.

NOTE!



The use of a firearm is exclusively permitted for proper use.

7. LIABILITY

J.G. ANSCHÜTZ GmbH & Co. KG assumes no liability or claims for damages of any type due to:

- Failure to follow these Manual
- Improper handling or repair
- Use of non-original ANSCHÜTZ parts
- Incorrect handling or maintenance
- Any type of carelessness
- Removal of seals or sealing lacquer
- Unauthorized interventions
- Transport damage that is not the fault of ANSCHÜTZ

can occur.

CAUTION!



Changes and manipulations to the firearm or its parts are prohibited and under some circumstances, may violate the guarantee provisions. Such changes can compromise the safe use of the product and cause accidents that put life and limb at risk. In such as case, the guarantee is automatically voided.

- ⚠ Examine the firearm for changes before each use.

8. PRODUCT-SPECIFIC HANDLING

8.1. BOLT

NOTE!



For some models, the rifle and the bolt are packaged separately for safety reasons and must be put together.

NOTE!



Before first use of the firearm, the bolt and inside of the barrel must be de-oiled lint-free.

8.1.1. COCKING THE BOLT

The bolt [6] must be cocked so that it can be installed in the receiver [7]. If the bolt [6] has been removed from the receiver and uncocked for cleaning or inspection [7], bolt [6] must be cocked manually before it is installed again. Cock the bolt [6] as follows:




Fig. 9 Bolt uncocked, firing pin "V3". Firing pin "V3" on page 11 not visible

V1. Firing pin spring

V3. Firing pin

4. Bolt handle

- Wipe excess oil from the bolt.

CAUTION!



Risk of injury!

- When cocking the bolt, make sure your fingers do not get caught!

- To do this, grip the firing pin spring [V1] firmly with your right hand and hold it fast. The bolt handle lock on the firing pin spring [V1] points forward to the left. The bolt handle [4] to the left downward.

- Now turn the bolt handle [4] clockwise, the firing pin spring [V1] counter-clockwise until an audible snap-in sound is heard.
- The cocked bolt [6] is indicated by the firing pin [V3] protruding toward the back.
- Alternatively, the bolt [6] can also be fixed in the vice.



Fig. 10 Hand position for uncocked bolt




Fig. 11 Hand position for cocked bolt




Fig. 12 Bolt cocked - firing pin [V3] visible

- ✓ The bolt [6] is now cocked and can be installed in the receiver [7].
- ✎ If the steps as shown in [Fig. 10] and [Fig. 11] cannot be done by hand, the bolt can alternatively be clamped. See [Fig. 13].
- ⚠ Make sure not to damage the bolt when cocking.




Fig. 13 Alternatively, the bolt can be clamped for these steps

8.1.2. INSERTING THE BOLT

WARNING!



Mortal danger!
Due to ammunition in chamber
or magazine.

- ▶ Make sure that no magazine is inserted
and there are no ammunition in the rifle.

CAUTION!



Property damage!

- ▶ When inserting the bolt, make sure not to
damage the stock.

NOTE!



To insert the bolt without resistance, the bolt-
catch [5] can be pressed. However, this is
generally not necessary.

- ▶ Place cocked bolt [6] on the receiver [7] and push the
bolt [6] forward (direction of arrow).



Fig. 14 Inserting the bolt

- ▶ Close the bolt [6], by pressing the bolt handle
downward [4] to the right.



Fig. 15 Closing the bolt handle

- ✓ The bolt [6] is inserted.
- ✓ The rifle is now cocked and ready to use.

8.1.3. REMOVING THE BOLT

CAUTION!



Property damage!

- ▶ When removing the bolt,
be sure not to damage the stock.

Here's how to remove the bolt [6]:

- ▶ Lift up the bolt handle [4] (direction of arrow) and pull
it back.



Fig. 16 Lifting the bolt handle

- ▶ Hold the bolt catch [5] down and pull the bolt [6] out
of the receiver.



Fig. 17 Removing the bolt

- ✓ The bolt [6] is removed.

8.2. MAINTENANCE OF THE BOLT

8.2.1. COMPONENTS/DEFINITIONS



Fig. 18 Bolt taken apart

- | | |
|-----------------------|-----------------|
| V1. Firing pin guide | V4. Receiver |
| V2. Firing pin spring | V5. Bolt handle |
| V3. Firing pin | V6. Plunger lug |

8.2.2. DISASSEMBLING THE BOLT

WARNING!



Only by an authorized gunsmith!

- ▶ Failure to follow these instructions voids the guarantee and any claims for damages.

- ▶ Removing the bolt (See chapter "8.1.3. Removing the bolt" on page 10).




Fig. 19 Bolt in cocked position after removal, Plunger lug [V6] visible

CAUTION!



Property damage!

When fixing the bolt, make sure that the bolt is not scratched or damaged.



Fig. 20 Cocked bolt fixed

- ▶ Turn the bolt in the direction of the arrow in order to put the bolt in the correct position for removing the bolt handle.
- ▶ For newer models from mid-2023 onwards, it is not necessary to move to the unlocked position [see Fig. 22].



Fig. 21 Turning the bolt to uncock it



Fig. 22 Position bolt handle to plunger lug

- Press the receiver [V4] in the direction of the firing pin guide [V1] and at the same time, pull the bolt handle [V5] out of the receiver [V4].




Fig. 23 Pulling out the bolt handle

- Pull out the firing pin [V3] with firing pin spring [V2] and firing pin guide [V1].




Fig. 24 Pulling out firing pin with spring

- ✓ The bolt [6] is now disassembled and can be cleaned.

NOTE!



Clean dirt and powder residues from all parts of the disassembled bolt with a thin, non-resinous oil. Then coat the components of the bolt with a light oil film.

8.2.3. ASSEMBLING THE BOLT

- Assembly is done in the reverse order.

NOTE!



The completely assembled bolt must be cocked before inserting it into the receiver. Cock the bolt (See chapter "8.1.1. Cocking the bolt" on page 9).

NOTE!



ANSCHÜTZ recommends having the head-space checked by an authorized gunsmith at regular intervals.

8.3. MAINTENANCE INTERVALS FOR BOLT

For optimal performance, ANSCHÜTZ recommends having the firing pin springs [V2] replaced by an authorized gunsmith every 5 years or after shooting 50,000 shots.

8.4. SETTING/RELEASING THE SAFETY

WARNING



The bolt handle lock has no influence on the safety! The bolt handle lock must be used independently of the safety!

NOTE!



The rifle's safety can only be set/released, e.g., with open bolt (firing pin cocked) or after the loading process/closed bolt (firing pin and trigger cocked). The general process "setting/releasing the safety" will be described below.

8.4.1. SETTING THE SAFETY

- Push the safety catch [3] to the back (in the direction of the arrow). The red dot is not visible.

NOTE!



The safety catch must catch in a notch exactly and may not be between the end stops.



Fig. 25 Safety catch "safe"

- ✓ The firearm is cocked and the safety set.
- ✎ The firing pin [V3] is visible.

8.4.2. RELEASING THE SAFETY

- Put the safety catch [3] in fire position (direction of the arrow). The red dot is visible.



Fig. 26 Bolt handle lock

- ✓ The firearm is cocked, released, and ready to fire (the red dot is visible).

8.4.3. BOLT HANDLE LOCK

With the bolt handle lock [2], it is possible to secure the bolt [6] against unintentional opening. It is above the safety [3] on the receiver [7].

- Models from mid-2023 onwards have a bolt handle lock with an additional safety button.

- Pressing the safety button and sliding the bolt handle lock [2] in the direction of the arrow locks the bolt [6]. The chamber can then not be opened or repeated either in the secured or unsecured state.



Fig. 27 Bolt handle lock deactivated, push forward to activate

- Deactivating of the bolt handle lock [2] in reverse order.



Fig. 28 Bolt handle lock activated, push to the rear to deactivate

- ⚠ Caution: The bolt handle lock must be released before the shot in order to be able to take a quick following shot.

8.5. LOADING/REPEATING/SHOOTING/UNLOADING

8.5.1. LOADING THE MAGAZINE

WARNING!



Mortal danger! Incorrect caliber in the magazine.

- Only use the caliber specified on the barrel.

CAUTION!



Only use ammunition with a muzzle speed V_0 of at least 280 m/s (920 fps). Failure to follow these instructions shall mean that the manufacturer assumes no liability and it voids the guarantee.

- ▶ Open the bolt [6].
- ▶ Set the firearm's safety!
(See chapter "8.4.1. Setting the safety" on page 13)

⚠ Only load the firearm immediately before use.

CAUTION!



Property damage!
After unlocking the safety, the magazine can fall out of the magazine guide of its own accord.

- ▶ While unlocking the magazine, hold a hand under the magazine.

- ▶ Press the magazine release lever [15] forward (in the direction of the arrow).



Fig. 29 Unlocking the magazine

- ▶ The magazine [16] is unlocked and can be removed.
- ▶ Use your hand to pull the magazine [16] out of the magazine guide.



Fig. 30 Removing the magazine

- ▶ Cartridges with cartridge rim in front, set in the middle of the feeder.




Fig. 31 Loading the magazine

- ▶ Press the feeder downward with the cartridge and push the cartridge into the magazine [16].



Fig. 32 Magazine loaded

- ✓ The magazine [16] is loaded

- ⚠ Only original ANSCHÜTZ magazines may be used.
- ⚠ The specified capacity of the magazine may never be exceeded.
- ⚠ Only cartridges of the caliber specified on the barrel may be used.
- ⚠ Only clean, factory-loaded, new ammunition in the caliber approved for the rifle may be used.
- ⚠ Ammunition must comply with the specifications of the C.I.P.

- ▶ Insert the magazine [16] into the firearm (in the direction of the arrow) until it audibly catches in a notch.
- ✎ For easier handling, you can press the magazine release lever parallel to this. The magazine then slides into the magazine guide with much less resistance.



Fig. 33 Inserting the magazine

- ☛ Chamber empty, full magazine in place, firing pin cocked, safety on.

8.5.2. REPEATING

WARNING!



Mortal danger!
Unintentional shooting due to loaded,
unsecured firearm.

- ▶ Hold the muzzle in a safe direction.
- ▶ After loading, set the firearm's safety.

WARNING!



Mortal danger!
Unintentional shooting due to inattention
when setting the firearm's safety or possible
malfunctions after setting the safety.

- ▶ Even when the safety is set, the muzzle
may never be held in a direction in which
it can cause damage or endanger life.

- ☛ Please note the condition of the bolt handle lock!

This rifle is a repeater, which feeds the ammunition directly from the loaded magazine. If you actuate the bolt, an armed cartridge is fed from the magazine into the chamber and the shot cartridge case is ejected first.

NOTE!



Any cartridge still in the chamber will be
ejected.

- ▶ If the bolt [6] is not open, open the [6].

NOTE!



By opening the bolt, the firing pin is cocked.

- ▶ Push the bolt [6] forwards and close the bolt [6].
This pushes the next cartridge out of the magazine [16]
into the chamber.



Fig. 34 Closing the bolt

- ▶ Make sure you act calmly and avoid shocks
so that the cartridge does not fall out of
the bolt body when closing.



Fig. 35 The firearm is loaded, cocked, and the safety set

- ✓ The firearm is loaded, cocked, and the safety set.

8.5.3. READY TO FIRE

WARNING



Mortal danger!

- ▶ Make sure that there is space in front of and behind you.
- ▶ Make sure that you have an appropriately safe bullet trap.
- ▶ Load and release the safety on your rifle only immediately before you are ready to fire.
- ▶ Set the safety or unload the rifle after shooting.

- ▶ The rifle is ready to fire after (See chapter "8.5.1. Loading the magazine" on page 13) and (See chapter "8.5.2. Repeating" on page 15). To shoot, actuate the safety catch [3] on the rifle and then carefully aim at the target and pull the trigger [13].
- ▶ To shoot again, lift up the bolt handle [4] and pull the bolt [6] up to the stud against the bolt catch [5].
- ☛ Please note the condition of the bolt handle lock [2]!
- ▶ The cartridge in the receiver [7] is ejected. By closing the bolt [6] again, the next cartridge slides out of the magazine [16] into the chamber.

NOTE!



By closing the bolt, the cartridge is fed into the chamber.

WARNING!



Mortal danger!
Unintentional shooting due to loaded, unsecured firearm.

- ▶ Hold the muzzle in a safe direction.
- ▶ After loading, set the firearm's safety.

WARNING!



Mortal danger!
Unintentional shooting due to inattention when setting the firearm's safety or possible malfunctions after setting the safety.

- ▶ Even when the safety is set, the muzzle may never be held in a direction in which it can cause damage or endanger life.

8.5.4. UNLOADING/MAKING READY FOR STORAGE

It is recommended that you keep the rifle with uncocked bolt [6]. This extends the life span of the firing pin spring and maintains reliable firing of the cartridge. Follow the steps below to make the repeater ready for storage.

- ☛ It is possible to load and unload this rifle in the safe position.

WARNING!



Mortal danger!
Unintentional shooting due to loaded, unsecured firearm.

- ▶ Hold the muzzle in a safe direction.
- ▶ Make sure that there are no ammunition in the magazine and the chamber before you perform this procedure.

Make sure that there are no ammunition in the magazine [16], the receiver, [7] or in the chamber. Check this as follows:

- ▶ Make sure that the safety catch [3] is on "safe" (the red dot is not visible).
- ▶ Lift up the bolt handle [4] and pull the bolt [6] up to the stud against the bolt catch [5].

NOTE!



Any cartridge still in the chamber will be ejected.



Fig. 36 Opening the bolt

- Press the magazine release lever [15] forward (in the direction of the arrow).



Fig. 37 Pushing the magazine release lever forward

- ✓ The magazine [16] is unlocked and can now be removed.



Fig. 38 Removing the magazine

- ☞ Before the next steps, check the magazine [16], the receiver [7], and the chamber.

CAUTION!



Property damage! After unlocking the safety, the magazine can fall out of the magazine guide of its own accord.

- While unlocking, hold a hand under the magazine.

- Put the safety catch [3] in fire position (direction of the arrow).



Fig. 39 Push the safety catch forward, press the trigger

- ✓ The red dot is visible.
- Hold the rifle in a safe direction and pull the trigger [13] to the rear position. This is best done with your left hand.
- Push the bolt [6] carefully forwards and close the bolt handle [4] slowly. This way, the firing pin inside the bolt can move safely forward and it reduces the pressure of the firing pin spring.



Fig. 40 Closing the bolt

- ☞ The firing pin is not visible.
- ✓ The firearm is now uncocked, unloaded, and ready for transport and storage.

8.6. TRIGGER

If your rifle has an adjustable trigger blade, you can adjust it as follows.

8.6.1. SINGLE STAGE TRIGGER 5082

Delivery state:

- ✦ The 5082 D trigger is delivered from the factory with a set trigger weight of 1,100 g.




Fig. 41 Single stage trigger 5082 Version 1




Fig. 42 Single stage trigger 5082 Version 2

- A1. Adjustment screw for trigger blade angle
- A2. Adjustment screw for trigger
- A3. Trigger blade

8.6.2. SETTING THE TRIGGER

8.6.2.1. ADJUSTING THE TRIGGER BLADE

Adjustment of the trigger blade [A3] for trigger 5082 D (model variant with 3 screws):

- Unscrew the trigger blade adjustment screw [A2] (2 mm hexagon screw), trigger blade [A3] can be pushed lengthwise along the guide.




Fig. 43 Adjusting the trigger blade

- Tighten the trigger blade set screw [A2] again. (2 Nm)
- ✓ Trigger blade [A3] is set.
- Unscrew the trigger blade adjustment screws [A1] (2 mm hexagon screw), trigger blade [A3] can be pushed lengthwise along the guide.





Fig. 44 Adjusting the trigger blade

- Tighten the trigger blade set screw [A1] again. (2 Nm)
- ✓ The trigger blade angle is adjusted.

Adjustment of the trigger blade for trigger 5082 D
(model variant with 2 screws):

- ▶ Unscrew the trigger blade adjustment screws [A1] (2 mm hexagon screw), trigger blade [A3] can be pushed lengthwise along the guide and angled to the side.



- ▶ Tighten the trigger blade set screws [A1] again. (2 Nm)
- ✓ Trigger blade and angle are set.

8.6.3. MAINTENANCE OF THE TRIGGER

- ☞ Please heed the general maintenance notes!
 - Keep trigger dry and dust-free (the release links were coated with long-lasting grease by ANSCHÜTZ).
 - Never wash out the insides of the trigger with a spray or oil to prevent hardening, sticking or soiling of the trigger parts.
- ⚠ When maintaining the firearm no dirt, solvent residues, greases or unsuitable oils may get into the trigger assembly.

8.6.4. CHECKING THE TRIGGER FASTENING

ANSCHÜTZ recommends checking before each use whether the trigger is securely fastened.

8.7. BARRELED ACTION MOUNTING AND STOCK SETTINGS

8.7.1. COMPONENTS/DEFINITIONS




Fig. 46 Main components of the model 1782



Fig. 47 Location of the bedding screws

- | | |
|----------------------|----------------------|
| 1. Stock | 16. Magazine |
| SY. Barreled action | SV1. Bedding screw 1 |
| SV2. Bedding screw 2 | |

8.7.2. MOUNTING/DISMOUNTING THE STOCK AND BARRELED ACTION

- ▶ Remove the magazine [16]
 - ▶ Loosen both bedding screws [SV1] and [SV2] completely (hexagon key 4 mm).
- ⚠ Important: Heed the sequence!**
When disassembling, first loosen [SV1], otherwise the barreled action and stock will jam. For mounting, follow the reverse order!
- ▶ Take the barreled action [SY] out of the stock [1].
 - ▶ The connection of stock and barreled action is done in the reverse order.
- ⚠** First tighten the front barreled action bedding screw [SV2] with 5 Nm, then the rear barreled action bedding screw [SV1] also with 5 Nm (both screws with hexagon 4 mm).

NOTE!



After initial mounting of the barreled action, settling may occur. That's why ANSCHÜTZ recommends tightening the bedding screws after a while.



The barreled action connection to the stock must be checked to ensure it is tight each time before you shoot.

8.7.3. STOCK ADJUSTMENTS

8.7.3.1. ADJUSTMENT OF THE CHEEK PIECE

NOTE!



Do not tighten the fastening screws too tightly to prevent damage to the threads.

If you have the Classic PRO or Black Line stock variant, you can adjust the cheek piece for this stock.

- ▶ To do this, loosen the adjustment screw on the right side of the stock with a 4 mm hexagon key.



Fig. 48 1782 Classic PRO and Black Line

- ▶ Then pull the cheek piece to the desired height.
 - ▶ Fix it by tightening the hexagon key on the right stock side. (2.5 Nm)
 - ▶ Make sure not to tighten the screw too much or you will damage the threads.
- ✓ The cheek piece is adjusted.

8.7.3.2. ADJUSTMENT OF THE STOCK LENGTH AND THE CHEEK PIECE OF THE GRS BIFROST STOCK

- ▶ Press the Speedlock II push buttons and adjust the stock length or cheek piece to the desired length or height.
- ▶ When the desired setting is reached, release the buttons.



Fig. 49 1782 GRS Bifrost

- ✓ The stock is adjusted.

8.7.3.3. MOUNTING OF THE SLING SWIVEL (OPTIONAL)

Your ANSCHÜTZ rifle comes with sling swivels for the mounting of your gun sling. Mount these as follows.

- ▶ Loosen the knurled screw.
- ▶ By pressing the knurled screw, free the bolts.
- ▶ Fold away the lock up.
- ▶ The bolts of the sling swivel can now be inserted into the sling swivel (studs) on the rifle stock.
- ▶ To close the lock up again, fold over the bolts and tighten the screw completely.



Fig. 50 Sling swivel

8.7.4. MAINTENANCE/CLEANING OF THE STOCK

- ☛ Please heed the general maintenance notes!

It is important to keep the stock clean and free of moisture. If your stock should get wet, we recommend cleaning it with a soft cloth and drying it completely. For this, it may be appropriate to dismount the stock and barreled action. Use only suitable cleaning and care products to maintain wood stocks.

NOTE!



Firearm oils are not suitable for stock maintenance. Use appropriate stock care products and note the instructions of the manufacturer in question.

NOTE!



Keep the stock dry, free of water, and avoid condensation formation. Pay attention that the stock does not come into contact with any solvents, cleaning products or other substances. Do not affix any stickers or other objects to the stock. This can cause damage to the stock surface.

NOTE!



Please note the cleaning instructions, the care products, and follow the instructions of the manufacturer in question.

8.8. BARREL/BARREL THREAD

8.8.1. DISMOUNTING/MOUNTING THE BARREL THREAD

If you want to clean the barrel thread and threaded bushing of an ANSCHÜTZ rifle, proceed as follows.

- Unscrew the threaded bushing from the barrel thread.



Fig. 51 Unscrewing the threaded bushing from the barrel thread

- Clean the barrel thread with a soft, lint-free cloth and a suitable cleaning solution.



Fig. 52 Cleaning the threads



Fig. 53 Coating with ceramic lubricant

- ✓ The barrel thread is clean.
- Clean the threaded bushing with a soft, lint-free cloth and a suitable cleaning solution.



Fig. 54 Cleaning and lubricating the threaded bushing

- ✓ The threaded bushing is clean.
- Mounting of the threaded bushing is done in the reverse order.

8.8.2. DISMOUNTING/MOUNTING THE BARREL

WARNING!



Only by an authorized gunsmith!

- Failure to follow these instructions voids the guarantee and any claims for damages.

Dismounting the barrel, e.g., for cleaning, is done by loosening two screws on the barreled action.

- First separate the stock and barreled action (See chapter "8.7.2. Mounting/dismounting the stock and barreled action" on page 20).
- Unscrew both pivot screws from the receiver with a 5mm hexagon key.



Fig. 55 Unscrewing the pivot screws

- For models starting with the end of 2022, depending on the design, it may be necessary to unscrew **two** additional screws. Unscrew these with a 2.5 mm hexagon key.



Fig. 56 Loosen countersunk screws

- ▶ The barrel can now be removed to the front for maintenance and cleaning purposes.



Fig. 57 Removing the barrel

- ▶ Assembly is done in the reverse order.
- ▶ The groove in the barrel and guide pin on the receiver must be flush.




Fig. 58 During assembly, the groove and guide pin must be flush

- ▶ Tighten the pivot screws with 6 Nm.
 - ▶ Tighten the countersunk screws with 2.5 Nm.
- ⚠ Important: First tighten the rear screw, then the front one. After this procedure, tighten the rear screw again.

8.8.3. MAINTENANCE OF THE BARREL

- ☞ Please heed the general maintenance notes!

8.8.3.1. CLEANING THE BARREL

CAUTION!



Never pull the brush back and forth in the barrel.

NOTE!



Heed the Manual of the cleaner!

NOTE!



After using cleaning agents that contain ammonia, be sure to re-oil the barrel to prevent the risk of corrosion.

To clean the barrel [8] in case of light soiling, use a synthetic brush.

- ▶ Oil the synthetic brush slightly and push from the chamber side out with a suitable cleaning rod through the barrel [8].
- ▶ To clean the barrel [8] in case of heavy soiling, use a bronze brush and a suitable barrel cleaner.



Fig. 59 Synthetic brush




Fig. 60 Bronze brush

- ▶ To dry the barrel, pull a woolen swab through the barrel [8] several times.
- ✓ The barrel [8] is clean.

8.9. SIGHTS/MOUNTING

8.9.1. ADJUSTING THE FAST ACQUISITION SIGHT

If your rifle should be equipped with a fast acquisition sight (open sight), adjust it as follows:




Fig. 61 Front sight of the fast acquisition sight

- ▶ If the result is a low shot, turn the screw on the front sight counter-clockwise step by step.
- ✓ The shot point shifts upward.
- ▶ If the result is a high shot, turn the screw on the front sight clockwise step by step.
- ✓ The shot point shifts downward.
- ▶ To adjust the shot point position horizontally (right/left), unscrew the screw in front of the rear sight.



Fig. 62 Rear sight of the fast acquisition sight

- ▶ If you have a left shot as result, slide the rear sight to the right step by step.
- ✓ The shot point shifts to the right.
- ▶ If you have a right shot as result, slide the rear sight to the left step by step.
- ✓ The shot point shifts to the left.

There is a front sight cover included with your rifle for the mounted front sight. It can be mounted as described below:

- ▶ Push the front sight cover from the rear over the base of the front sight into the notch intended for this.




Fig. 63 Mounting the front sight cover

- ▶ For this, the front sight cover must be spread a bit with a spreader.



Fig. 64 Spreader



Fig. 65 Front sight cover on spreader

- ▶ The front sight cover snaps into the final position.
- ✓ The front sight cover is mounted.



Fig. 66 Front sight with mounted front sight cover



Fig. 67 Sighting line with and without front sight cover

9. MAINTENANCE/CLEANING

9.1. GENERAL

WARNING!



Mortal danger!

Mortal danger! due to loaded firearm.

- Before use, or in case of maintenance and cleaning work, ensure that the firearm is not loaded. It is recommended that you remove all live ammunition from the work area when you are performing maintenance work on the rifle.

WARNING!



Bodily injury or property damage! Risk of bodily injury or property damage due to unoiled barrel and chamber.

- Before shooting, the barrel and the chamber must be free of foreign bodies.

CAUTION!



Any changes or damage to the firearm should always be heeded. In case of a change or damage, the firearm must be brought immediately to an authorized gunsmith or sent to ANSCHÜTZ for inspection.

NOTE!



Protect the firearm against dust, sand, moisture, heat, and damaging influences.

NOTE!



In order to reduce the risk of stock breaks during transport, ANSCHÜTZ recommends, especially for flights, detaching the barreled action from the stock.

NOTE!



Please clean your rifle – especially the bolt and the barrel – after each use if you are using a sound moderator. Also follow the cleaning instructions of the manufacturer of your sound moderator!

NOTE!



Dry firing:

For safety, during dry firing, please always use a buffer cartridge to prevent damage!

NOTE!



When cleaning plastic parts (e.g., magazine floors, feeder), use only oils that do not damage, attack or destroy the plastic!

NOTE!



The rifle case/soft case should be cleaned and freed of dust and lint regularly.

The rifle case and soft case should have a smooth, dust-resistant inner lining.

When the rifle is not being used, the rifle case/soft case should always be open in order to allow moisture to escape.

The insertion of a moisture trap can reduce moisture formation.

NOTE!



Keep the stock dry, free of water, and avoid condensation formation. Pay attention that the stock does not come into contact with any solvents, cleaning products or other substances.

Do not affix any stickers or other objects to the stock. This can cause damage to the stock surface.

NOTE!

If nothing else is specified, please tighten screws only hand-tight to prevent damage!

NOTE!

When inserting the bolt, make sure not to damage the stock! Incorrect handling and inattention do not constitute a warranty case.

NOTE!

After each use of the firearm, coat the steel parts with a thin oil film and clean the barrel thoroughly.

When transporting from cold to warm rooms, condensation can form on metal parts and inside the barrel. If this condensation is not dried off quickly, it can cause flash rust under some circumstances.

No other tools (felt stoppers, unapproved greases, etc.) may be used for cleaning the barrel.

9.2. MAINTENANCE INTERVALS**9.2.1. BEFORE SHOOTING**

- Remove oil from the firearm carefully.



Removing oil from the firearm should be done at room temperature since at cold temperatures, too much residue may remain in the barrel.

- Shoot one to two shots to restore even shooting performance (oil shots).

9.2.2. AFTER SHOOTING

- Allow the firearm to warm up to room temperature with the bolt and snow cover (if present) open.
- Carefully remove sweat from external parts.
- Take the firearm apart and clean sweat off individual parts as well.
- Oil firearm with suitable gun oil, oil stock with special stock care products.
- Clean the barrel with a plastic brush and gun oil.

**For new rifles (up to 100 shots)
in 10-shot intervals, following in
min. 50-shot intervals**

- Clean the barrel from the chamber to the muzzle with a brass or bronze brush with suitable barrel cleaner.



Do not pull the brush back and forth in the barrel.

- Unscrew brass brush outside the muzzle and pull the cleaning rod carefully back through the barrel.
- Pull the cotton wick several times dry through the barrel until the last cotton wick no longer indicates any noticeable soiling.
- Wipe off the firearm (incl. stock) with an oily cloth.

9.2.3. ANNUALLY

- Have the firearm checked once a year by an expert who has received training from ANSCHÜTZ about the maintenance of ANSCHÜTZ firearms!

10. TROUBLESHOOTING

CAUTION!



In case of malfunction (shots not fired, etc.), the rifle must be unloaded, the safety set, and it must be brought to a specialized dealer/gunsmith or sent to ANSCHÜTZ.

11. DISPOSAL



Disposal of the firearm must be done demonstrably by a specialized dealer/gunsmith.

12. MISCELLANEOUS

Additional information is available on the Internet at www.anschuetz-sport.com. ANSCHÜTZ will also be glad to inform you about news about this and other products with the ANSCHÜTZ newsletter, to which you can subscribe for free on the Internet.

Included with your firearm is a quality control card with the original test fire group.



Fig. 68 Control card shot with premium hunting ammunition (Fig. similar)

NOTE!



Please wash your hands for hygienic reasons each time after you use the rifle, as there can be oils, greases, and contamination on the rifle.

13. SHOOTING PERFORMANCE

The shooting performance of a rifle depends on many factors. An important factor here is the ammunition. Not every barrel shoots equally well with every type of ammunition; there can be significant differences in performance.

The sights and their mounting is just as important. Parallax, loose sighting, defects in the sighting adjustment, and non-optimal mounting are the most frequent causes of unsatisfactory shooting performance.

That's why only telescopic sights and mounts mounted by a specialist are used and the ammunition is coordinated with those on your rifle.

Even ammunition from the same maker and the same filling can produce different shooting performance and shooting patterns from batch to batch and rifle to rifle. With optimally selected ammunition, sights, and mounting, we guarantee the outstanding shooting performance of our rifles.

See guarantee card.

Please also note that every attachment or accessory (regardless of the manufacturer), such as sound moderators, muzzle brakes, and sights contribute to the precision and shooting performance and can affect it.

NOTE!



Every bolt is adapted to the associated rifle in order to achieve optimal shooting performance. This is why, and for safety, the bolts may not be exchanged.

14. GUARANTEE CARD

ANSCHÜTZ

EINFACH EINS WERDEN!

<<< **WARRANTY** >>>**1. Material:**

This product has been released for sale after the product itself, its materials and individual components have been subjected to strict inspection, or the rifle has demonstrated its durability and function during test shooting. J.G. ANSCHÜTZ GmbH & Co. KG offers a full guarantee covering material and manufacturing faults (excluding broken stocks and springs) for a period of two years, provided that the fault can be shown to have been present at the time of handover of the product. No warranty claims will be accepted by J.G. ANSCHÜTZ GmbH & Co. KG for faults that are the result of improper use or unauthorised repairs. The item will either be repaired or replaced at our discretion. Claims for compensation - put forward for any legal reason whatsoever - are excluded.

2. Shooting Performance:

The purchaser undertakes to inform J.G. ANSCHÜTZ GmbH & Co. KG in writing of any faults detected in shooting performance within one month of purchase with the submission of their own shooting record. J.G. ANSCHÜTZ GmbH & Co. KG reserves the right to transfer the rifle to an independent agency for inspection (DEVA or a national ballistics office). Should such an agency confirm excellent shooting performance, J.G. ANSCHÜTZ GmbH & Co. KG is entitled to charge the purchaser the costs of the rifle inspection. The accepted warranties do not apply to rifle damage resulting from mechanical effects and improper use or care by the purchaser. The warranty is excluded if the rifle has been repaired or modified by unauthorised persons. Likewise, the warranty is cancelled when using reloaded ammunition or ammunition which is not CIP approved.

In the event of a warranty/damage claim please enclose this card, completed and signed by your dealer, with the product.

J.G. ANSCHÜTZ GmbH & Co. KG · Jagd- und SportwaffenfabrikPostfach 1128 · D-89001 Ulm/Germany · www.anschuetz-sport.com**Serial-No.:****Date:****Bought at:**

ANSCHÜTZ

EINFACH **EINS** WERDEN!

J.G. ANSCHÜTZ GmbH & Co. KG
Jagd- und Sportwaffenfabrik

Daimlerstraße 12 · 89079 Ulm / Germany

Tel. +49 - (0)731 - 40 12 - 0


Fax +49 - (0)731 - 40 12 - 700

www.anschuetz-sport.com

www.facebook.com/OfficialAnschuetz

www.youtube.com/AnschuetzGmbH

www.instagram.com/AnschuetzGmbH



Production and model changes reserved · All colors and sizes approximate · Firearms that require a permit: Supply of firearms only to the holders of a purchasing permit ·
Firearms that do not require a permit: Supply only to persons over 18 years of age.
Misprints, errors, and prior sale also reserved © ANSCHÜTZ